

ädese

Distinctive elegance, Superior technology

With Odyssey™, SAFLOK® has blended distinctive elegance and superior locking technology.

Compatible with SAFLOK's System 6000™ front desk operating system and Messenger™ wireless lock access network, this premier electronic lock is masterfully crafted for the world's most prestigious hospitality properties creating a revolutionary access management system.

Advanced Engineering

Odyssey's custom circuit assembly includes an Intel processor, real-time clock, diagnostic circuitry, and software. All components are embedded in silicone to prevent moisture intrusion.

The FLASH memory stores more than a year's worth of lock data—as many as 5,900 entries. It provides audit information such as time and date of entry, as well as the ID code of the employee or guest using the keycard. Odyssey records entry into and egress from the room.

Used in conjunction with Messenger, Odyssey's "door ajar" feature remotely alerts the front desk whenever a door has been left open. This egress and ingress capability saves hours of manually checking to see that room doors are securely closed.





Odyssey's battery pack is solid soldered and insulated to ensure uninterrupted power. If the battery power is running low, an automatic alert is activated via a red light that is displayed with insertion of the keycard. This signal is given months before the battery needs to be replaced. If Messenger is employed, a low battery message is displayed on the computer screen months in advance. The programming and audit function remain intact during change-out.

Passage Mode

Compatible with access management systems that use magnetic stripe, smart card or memory card technology, Odyssey can be programmed to lock and unlock at targeted times allowing unrestricted entry during "passage" hours. Otherwise, the lock engages. This feature makes Odyssey ideal for perimeter, meeting room, and amenity area doors.

Flawless Finishes

Odyssey is available in seven durable, flawless finishes: satin chromium; satin or bright brass; polished, satin or pearl nickel; and oil-rubbed bronze. All of these finishes come with a variety of matching lever finishes and complementary lever designs.

To maintain the original luster and color, most of Odyssey's finishes contain EHCTM— Environmentally Hardened Coating— that provides exceptional resistance to corrosion and abrasion. Perennially, Odyssey will maintain its original luster and color.

Odyssey's sleek design, curved edges, and flawless finishes complement the changing architectural and design demands of the luxury hospitality market. SAFLOK also replaced the LED access indicator lights of its previous lock models with an illuminated keycard slot to reinforce its clean, sophisticated façade.

Optional Automatic Dead Bolt (ADB™)

The SAFLOK automatic dead bolt has a two-point locking system. The 3/4" dead locking latch and 1" steel reinforced dead bolt engage with every door closing.

Optional Communication Technology

SAFLOK's optional communication technology (available only with the System 6000 front desk operating system) enables the Odyssey lock to become part of a centralized access control and communication system including interfacing with the Messenger wireless lock access network and the Inncom energy management system.

Safe and Secure with SAFLOK

SAFLOK technical experts are available 24 hours a day, seven days a week for support.

A worldwide leader in the development and manufacture of electronic lock systems, SAFLOK will help you achieve the highest levels of security, efficiency, and flexibility in your daily operations. The premier provider of state-of-the-art security programs for more than 25 years, SAFLOK has earned a stellar reputation for continuous quality improvement.

SAMPLE FINISHES (Actual finish color may differ slightly from printed example. Architectural codes indicated refer to BHMA numbers.)



SPECIFICATIONS (Odyssey is designed to accommodate an ASA 4 7/8" (125 mm) strike plate.)

- · Mortise lock available in standard function, ADB function with 1" (25 mm) throw dead bolt, and 3/4" (19 mm) dead locking latch bolt
- · 2-3/4" backset
- · Operates on standard AA alkaline battery pack
- · Door thickness range 1-3/4" 2-1/8" for standard product
- · "Door ajar" sensing mortise

Options:

- · Custom designs available for thicker doors
- Escutcheon: 10-1/4" (260 mm) x 3-1/2" (89 mm)
- · Armored front: 8" (203 mm) x 1-1/4" (32 mm) or 8" (203 mm) x 1-1/16" (27 mm)
- · Compatible with Messenger wireless lock access network
- * Lever may not be suitable for use in all areas. Check local fire code.
- ** EHC finish not available.

Certification:

- · ANSI 156.13-2002 American National Standard for mortise locks and latches. Grade one level for both security and operational requirements
- · ANSI 156.25-2002 American National Standard for electrified locking devices
- · Certified by Underwriters Laboratories (UL) for use on fire doors up to 3-hour rating
- · Accessibility Code (ADA) A117.1 for all levers

When ordering please specify:

- · Total number of lock sets and spares
- · Desired finish
- · Door thickness and composition (wood or metal)
- · Door preparation consult SAFLOK for template
- · Door frame composition wood or metal frame and strike plate measurements

HANDLE STYLES



- * Only standard handle available in EHC and standard finishes. No upcharge or additional lead time required
- ** Levers in EHC finish available at an upcharge and requires additional lead time. Non-EHC finishes do not require an upcharge or additional lead time
- *** Not available in an EHC finish





















For worldwide office locations and contact information, visit us at www.Saflok.com.

Americas

Phone: 877.272.3565 Global Headquarters: Troy, MI, USA

Europe · Middle East · Africa Phone: 00.32.3.766.00.20

Asia Phone: 021.5868.1481 Manufactured under one or more of the following patents: U.S.: 4.177.657: 4.411.144: 4.534.194: 4.890.870: 5.198.643: 5,477,041; 5,820,177; 5,986,564; 7,051,561; D494,841; D501,131 D512,899; D519,021 CANADA: 1,252,854; 1,298,902 U.K. 2,010,375 Other U.S. and foreign patents pending

> SAFLOK reserves the right to modify the characteristics and features of all products in this publication. ©2007 SAFLOK, all rights reserved.